



H-Frame 2- Point Crankless (HE2P) Capacity(Ton) : 400 ~ 1500

- ☛ **HIM** Made in South Korea
- ☛ Solid type of Eccentric drum and Main gear is rigid enough against torsion, which enable
- ☛ Semi-permanent function without any change in precision degree.
- ☛ Seat metal(horse shoe metal) on contact part in between Rod and Plunger enables high precision and durable work.
- ☛ Plunger guide prevents driving parts from oil leakage and it also minimize eccentric load by eliminate thrust load
- ☛ Wet type clutch/brake(seperated) with no noise and dust enables soft and semi-permanent function..
- ☛ Low noise and vibration by gear heat treatment and grinding.
- ☛ Phase angle is adjusted by key type, which eliminates phase contrast.

SPECIFICATION

MODEL ITEM	UNIT	HE2P-400	HE2P-500	HE2P-600	HE2P-800	HE2P-1000	HE2P-1200	HE2P-1500
Capacity	Ton	400	500	600	800	1000	1200	1500
Rated Tonnage Point Above (B.D.C)	mm	13	13	13	13	13	13	13
Stroke Length	mm	600	600	600	600	600	600	600
No. of Stroke	S.P.M	10 ~ 20	10 ~ 20	10 ~ 20	10 ~ 20	10 ~ 20	10 ~ 20	10 ~ 20
Die Height	mm	1200	1200	1200	1200	1200	1200	1200
Slide Adjustment	mm	600	600	600	600	600	600	600
Slide Area(LRxFB)	mm	2800 x 1600	2800 x 1600	2800 x 1600	2800 x 1600	2800 x 1600	3000X1600	3400X1600
Bolster Thickness	mm	2800 x 1600	2800 x 1600	2800 x 1600	2800 x 1600	2800 x 1600	3000X1600	3400X1600
Main Motor	Kw x p	55 x 4	75 x 4	90 x 4	110 x 4	135 x 4	185 x 4	220 x 4