



High Speed Precision (HIHP) Capacity(Ton) : 20 ~ 75

- ✦ **HIM** Made in South Korea
- ✦ Adapt Oil Crank Clearance system
- ✦ Attach Dynamic Balance Devices
- ✦ Frame of High Strength

SPECIFICATION

MODEL ITEM	UNIT	HIHP-20			HIHP-35			HIHP-50			HIHP-75		
Capacity	Ton	20			35			50			75		
Stroke Length	mm	10	20	30	20	30	50	20	40	60	30	50	80
No. of Stroke	S.P.M	150~600	150~500	150~400	150~500	150~400	150~300	150~450	150~350	150~300	150~350	150~300	150~200
Die Height	mm	200	195	190	255	250	240	280	270	260	300	290	275
Slide Adjustment	mm	50			55			60			70		
Slide Area(LRxFB)	mm	270x160			320x200			420x270			520x310		
Bolster Area (LRxFB)	mm	600x350x80			710x400x100			800x500x110			940x540x130		
Bolster Opening	mm	140x60			160x80			200x100			300x150		
Shank Hole	mm	φ32 x 55L			φ38 x 60L			φ50 x 65L			φ50 x 70L		
Main Motor	Kw x p	3.7 x 4			5.5 x 4			7.5 x 4			11 x 4		
Bed Opening	mm	280x200			320x240			400x320			500x400		
Air Pressure	Kg/cm ²	5			5			5			5		